








Raman amplified optical transmission system with reduction of four wave mixing effect

Patent number: EP1130825
Publication date: 2001-09-05
Inventor: HANSEN PER BANG (US); LEE ROBERT B (US); PARK SEO Y (US); REED WILLIAM ALFRED (US); STENTZ ANDREW JOHN (US)
Applicant: LUCENT TECHNOLOGIES INC (US)
Classification:
- international: **H01S3/30; H04B10/17; H04B10/18; H01S3/30; H04B10/17; H04B10/18; (IPC1-7): H04B10/17; H01S3/30; H04B10/18**
- european: **H01S3/30F; H04B10/17R; H04B10/18N4**
Application number: EP20010301455 20010219
Priority number(s): US20000186793P 20000303; US20010772489 20010130

Also published as:

 US6697558 (B2)
 US2001036347 (A)
 EP1130825 (A3)
 CA2335891 (A1)

Cited documents:

 EP0798578
 US5887105
 XP000966779

Report a data error here**Abstract of EP1130825**

A transmission fiber for use in a Raman amplified optical communication system is formed to exhibit certain characteristics that limit modulation instability and four-wave mixing in the amplification region, thus reducing the noise component present in the transmission system. In particular, the group-velocity dispersion (denoted as D and measured in terms of ps/nm-km) is restricted to be either non-positive or greater than +1.5ps/nm-km in the pump wavelength range of interest (a typical pump wavelength range being 1430-1465nm). Preferably, the magnitude of the dispersion is kept below a value of 10 ps/nm-km in the signal wavelength range of interest (e.g., the "C" band or "L" band). Four-wave mixing is reduced by ensuring that the zero-dispersion frequency of the transmission fiber is not centered between the pump frequency and a frequency experiencing Raman gain.

Data supplied from the **esp@cenet** database - Worldwide